

## REPORT DOCUMENTATION PAGE

0410

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering the required data, reviewing the collected data, completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE 01-09-2002	2. REPORT TYPE Final Report	3. DATES COVERED from 1 June 01 to 31 Dec 03
4. TITLE AND SUBTITLE  Multiscale statistical models for signal and image processing		5a. CONTRACT NUMBER
		5b. GRANT NUMBER F49620-01-1-0378
		5c. PROGRAM ELEMENT NUMBER
5. AUTHOR(S)  Richard G. Baraniuk		5d. PROJECT NUMBER
		5e. TASK NUMBER
		5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  Rice University 5100 Main Street Houston, TX 77005		8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  Air Force Office of Sponsored Research (AFOSR) Jon Sjogren 801 North Randolph Street Room 732 Arlington VA 22203-1977		10. SPONSOR/MONITOR'S ACRONYM(S) AFOSR
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)

## 12. DISTRIBUTION / AVAILABILITY STATEMENT

Unlimited

## 13. SUPPLEMENTARY NOTES

## 14. ABSTRACT

We are developing a general theory for multiscale signal and image modeling, processing, and analysis that is matched to singularity-rich data, such as transients and images with edges. Using a linguistic analogy, our model can be interpreted as *grammars* that constrain the wavelet *vocabulary*. Our investigation focuses on probabilistic graph models (tree-based hidden Markov models) that can accurately, realistically, and efficiently represent singularity structure in the wavelet domain. Grammar design is being guided by a detailed study of the fine structure of singularities using Besov spaces and multifractal analysis.

## 15. SUBJECT TERMS

20040810 022

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code)

8-4-04

---

**AFOSR Grant # F49620-01-1-0378**

**Final Report  
June 2004**

***Multiscale Statistical Models for Signal and Image Processing***

**Richard Baraniuk  
Rice University**

---

Department of Electrical & Computer Engineering  
6100 Main Street  
Houston, TX 77005

Tel: 713-348-5132  
Email: richb@rice.edu  
Web: dsp.rice.edu

**1. Objectives**

This project developed a new set of tools for multiscale signal and image modeling, processing, and analysis that are matched to singularity-rich data, such as transients and images with edges. Using a linguistic analogy, our models can be interpreted as *grammars* that constrain the wavelet *vocabulary*. Our investigation focused on probabilistic graph models (tree-based hidden Markov models) that accurately, realistically, and efficiently represent singularity structure in the wavelet domain. Grammar design was guided by a detailed study of the fine structure of singularities using Besov spaces and multifractal analysis.

**2. Research Findings**

*Complex wavelet vocabulary*

Signal and image processing algorithms based on the fully decimated wavelet transform suffer from *shift-variance*, reducing their power considerably. Shift variance dilutes the power of any model for the wavelet coefficients because the model must tolerate the strong changes in wavelet coefficient structure as the signal is shifted. Hence, we developed models for the *complex wavelet transform* (CWT). The dual-tree CWT analyzes a signal or image in terms of two wavelets that are close to a Hilbert transform pair (90 degrees out of phase, like a cosine and sine). The complex magnitude of the CWT is very nearly shift-invariant and in 2-d also features improved angular resolution (six oriented subbands at multiples of 15 degrees over the standard wavelet transform's three).

We extended our wavelet hidden Markov tree (HMT) modeling framework to the magnitude of the CWT. The complex HMT model is computationally efficient (with linear-time computation and processing algorithms) and applicable to general Bayesian inference problems as a prior density for images. (See the Figures at the end of this report.)

Modeling both the magnitude and phase of the complex wavelet transform enables us to perform *coherent processing* in the wavelet domain analogous to coherent processing in the Fourier domain. Our experiments indicate that large gains in denoising, classification, and compression performance should result.

### *Edge geometry modeling*

The magnitude and phase of the complex wavelet transform have natural interpretations in terms of image edges. Given an edge passing through a complex wavelet's support, the magnitudes of the six complex wavelet coefficients at that scale and position can be interpolated to accurately indicate the *angle* of the edge. The *phase* of the largest magnitude coefficient indicates the edge's offset from center. This relationship has allowed us to build Markov models to describe the evolution of image edges in a multiscale fashion. (See the Figures at the end of this report.)

### *Orthogonal complex wavelets*

The dual-tree CWT analyzes in terms of a tight frame of redundancy 2 in 1-d and 4 in 2-d. For maximum efficiency, it is reasonable to ask whether it is possible to construct useful complex wavelets with no redundancy. By "useful" we mean complex wavelets whose coefficients have easily modeled structure. Working in a 3-band (rather than the classical 2-band) filterbank structure, we have developed a new non-redundant CWT whose coefficients reflect the attractive properties of the redundant 2-band CWT.

## **3. Accomplishments**

### *Complex HMT denoising*

We successfully applied the complex wavelet HMT model in two relevant problems. In estimation ("*denoising*"), the complex wavelet HMT model outperformed all known wavelet denoising algorithms, including redundant wavelet thresholding (cycle spinning). A multiscale maximum likelihood *texture classification algorithm* produces fewer errors with the new model than with a traditional real wavelet HMT. (See the Figures at the end of this report.)

### *Edge geometry compression*

We developed a prototype *image compression algorithm* based on this framework that encodes the image geometry description and the residual texture information jointly in a rate/distortion optimal fashion. The algorithm outperforms the new JPEG2000 by a fairly significant margin (up to 1-2dB in PSNR for "edgy" images). Indeed, we have proved that for a simple class of "piecewise smooth" cartoon images consisting of smooth ( $C^2$ ) regions delineated by smooth ( $C^2$ ) edges, that this algorithm is *near-optimal in a rate/distortion sense*. That is, the mean-squared error  $D$  of image approximation decays with the number of bits  $R$  as  $D(R) \sim C (N/\log N)^{-2}$ .

Finally, since the compressed bit stream contains explicit geometry information regarding edges, it could prove very useful for efficient image classification and data base searching. This new framework demands further investigation. (See the Figures at the end of this report.)

Both of these innovations have been transferred to Texas Instruments for possible incorporation into next-generation wavelet-based image processing systems.

#### **4. Personnel Supported**

Richard Baraniuk (PI)  
Hyeokho Choi (senior researcher; equivalent to postdoc)  
Justin Romberg (graduate student)

In addition NSF Graduate Fellow Michael Wakin contributed significantly to this effort at no charge to the grant.

#### **5. Technical Publications**

All papers are available at the Rice DSP web site at *dsp.rice.edu/publications*

##### *5.1 Journal Publications*

M. Wakin, J. K. Romberg, H. Choi, and R. G. Baraniuk, "Wavelet-domain Approximation and Compression of Piecewise Smooth Images," submitted to IEEE Transactions on Signal Processing, 2004.

H. Choi and R. G. Baraniuk, "Multiple Wavelet Basis Image Denoising using Besov Ball Projections," to appear in IEEE Signal Processing Letters, 2004.

R. V. Gaikwad and R. G. Baraniuk, "Optimal Signaling Strategies for Communication in the Presence of Cross-talk," IEEE Transactions on Communications, July 2004.

R. Neelamani, H. Choi, and R. G. Baraniuk, "ForWaRD: Fourier-Wavelet Regularized Deconvolution for Ill-Conditioned Systems," IEEE Transactions on Signal Processing, 2003.

R. L. Claypoole, G. Davis, W. Sweldens, and R. G. Baraniuk, "Adaptive Wavelet Transforms for Image Coding using Lifting," IEEE Transactions on Image Processing, December 2003.

R. G. Baraniuk, R. A. DeVore, G. Kyriazis, and X. M. Yu, "Near Best Tree Approximation," Advances in Computational Mathematics, vol. 16, pp. 357-373, 2002.

T. D. Dorney, W. W. Symes, R. G. Baraniuk, D. M. Mittleman, "Terahertz Multistatic Reflection Imaging," Journal of the Optical Society of America, Vol. 19, No. 7, July 2002.

## 5.2 *Reviewed Conference Proceedings*

M. Wakin, J. Romberg, H. Choi, and R. G. Baraniuk, "Image Compression using a Cartoon+Texture Image Model," *Digital Compression Conference*, Snowbird, Utah, 2002.

M. Wakin, J. Romberg, H. Choi, and R. G. Baraniuk, "Rate-Distortion Optimized Image Compression using Wedgelets," *IEEE ICIP* 2002.

M. Wakin, J. Romberg, and R. G. Baraniuk, "Multiscale Wedgelet Image Analysis: Fast Decompositions and Modeling," *IEEE ICIP* 2002.

35 more – see [dsp.rice.edu/publications](http://dsp.rice.edu/publications) and [dsp.rice.edu/~richb/bio.html](http://dsp.rice.edu/~richb/bio.html)

## 6. *Interactions / Transitions*

### 6.1 *Conference Presentations*

See above Conference Proceedings.

### 6.2 *Transitions*


Transitioned complex wavelet algorithms to Texas Instruments (Dr. Felix Fernandes, [felixf@ti.com](mailto:felixf@ti.com)) and to Raytheon (Dr. Harry Schmidt). We also have posted software for many of these new algorithms on our web site at [dsp.rice.edu/software](http://dsp.rice.edu/software)

## 7. **Patent Disclosures**


None.

## 8. **Honors**

- Elected Fellow of the IEEE
- Co-Author on *Passive and Active Network Measurement Workshop* Student Paper Award
- Co-Author on *IEEE Signal Processing Society* Junior Paper Award (with M. S. Crouse and R. D. Nowak)
- *IEEE NORSIG* Best Paper Award (with E. Monsen, J. Odegard, H. Choi, J. Romberg), 2001
- George R. Brown Award for Superior Teaching (Rice, twice)
- ECE Young Alumni Achievement Award (University of Illinois)
- Charles Duncan Junior Faculty Achievement Award (Rice)




*1-d complex biorthogonal wavelet, with even-symmetric real part (blue)  
and odd-symmetric imaginary part (red).*




*2-d complex wavelets analyze at 6 different orientations,  
all multiples of 15 degrees*


noisy, 20.2 dB





HMT, 28.6 dB



CHMT, 29.3 dB




*Our complex wavelet HMT denoising algorithm outperforms all other wavelet denoising algorithms in the literature (figures are PSNR). Note especially the clean edges and ridges in the complex wavelet HMT (CHMT) estimate.*



*Our multiscale edge geometry model builds up smooth image edges from straight line segments (a la Donoho's wedgelets). A multiscale Markov model on the segments enables a fast dynamic program on the wedgelet quad-tree to find the optimal balance between the sparsity of the representation (a few large edge segments) and accuracy (requiring many small segments).*

*Due to the Markov probability model, this method significantly outperforms Donoho's CART-based representation.*






*The CWT enables accurate and efficient algorithms for identifying edges and estimating their parameters. In this example, four square blocks from the image on the left have been analyzed in terms of their CWT coefficients. Using the CWT magnitudes to estimate the edge orientations and the phases to estimate the offsets, we approximate these blocks by piecewise constant wedgelets at right.*

state-of-the-art  
SFQ  
wavelet image  
coder  
(zoom)



new  
WSFQ  
wavelet/wedgelet  
image coder  
(zoom)



*Comparison of state-of-the-art SFQ wavelet-based image coder versus the new WSFQ coder based on wavelets and wedgelets (zoom).*